

A3
 decoded information is input to the port is then detected. In response to detection of the input of the encoded information, the user computer is connected to the second location utilizing the decoded information.--

IN THE CLAIMS

Please delete Claims 1-21 in the present application and insert the following claims:

Sub E17
 --22. A method for connecting a user computer at a first location on a network with a second location on the network through use of a coded symbol having contained therein encoded information associated with routing information on the network to the second location thereover, comprising the steps of:

A4
 extracting the encoded information from the coded symbol and decoding such extracted encoded information to provide decoded information;

inputting the decoded information to a defined port on the user computer which has an existing first functionality associated with the operation of the user computer which is not the same functionality as the step of inputting the decoded information, such that the step of inputting comprises a second functionality, with the port of the user computer operable to accommodate for both the first and second functionality during operation thereof;

detecting operation under the second functionality when decoded information is input to the port; and

in response to the step of detecting, connecting to the second location utilizing the decoded information.--

--23. The method of Claim 22, wherein the network comprises the Internet.--

merd17
code.--

--24. The method of Claim 22, wherein the decoded symbol comprises a bar

--25. The method of Claim 24, wherein the bar code includes a UPC.--

--26. The method of Claim 24, wherein the bar code includes coded therein an ISBN code.--

--27. The method of Claim 24, wherein the bar code contains therein an EAN code.--

--28. The method of Claim 22, wherein the coded symbol is disposed on a product.--

--29. The method of Claim 28, wherein the encoded information comprises information related to the product and is unique thereto.--

--30. The method of Claim 22, wherein the coded symbol comprises an optical symbol and the step of extracting comprises optically scanning the encoded information.--

--31. The method of Claim 22, wherein the step of connecting comprises the steps of:

interfacing the user computer through the network to an intermediate location on the network having a resource server and a resource database disposed thereat;
transmitting the decoded information to the interface with intermediate locations;
the database having stored therein a table of routing information and a

10 comparing the received decoded information with the stored decoded
information and, if there is a match, transmitting the associated routing information with the
matched decoding information back to the user computer; and

A4

providing an input device for performing the operation of extracting,
wherein the input device has associated therewith an input device ID; and

5

5

receiving the encoded information at the second input and decoding the received encoded information to provide decoded information at the single output of the wedge; and

converting the second functionality to the first functionality with the encoded